



INSTALLATION INSTRUCTIONS

LD3011

[Model 2007-2018 Silverado/Sierra 1500 Crew Cab Under Seat and 2007-2019 Silverado/Sierra 2500,35000 Crew Cab Under Seat Long Gun Safe]

1. For any combination style lock, it is a good idea to set the combination before installing the safe. We recommend that the combination be set with the **DOOR OPEN** in order to test the lock combination effectively without locking yourself out.
2. Lift up both seats in the rear of the cab of your vehicle.
3. Remove the neoprene padding or convoluted foam from the inside of the safe for now.
4. One each side of the rear seats, there is a stud with a nut holding the seat to the vehicle.
 - a. Place the **MAIN MOUNTING BRACKET** over the nut and tighten the **13mm** nut over the stud, making sure that the bracket is pointing directly forward.
 - b. Place the **COVER BRACKET** over the main bracket using the notch and tab to lock them together.
5. Place the safe over the **5/16"** stud and tighten the second included nut on the stud (make sure that the stud is through the slot in the safe, then tighten the nut over the stud).
6. Tighten the nuts, **DO NOT OVER TIGHTEN, THIS COULD DAMAGE THE VEHICLE OR THE SAFE.**
7. Re-insert the padding or foam that was removed from the safe before installation.
8. Enjoy your purchase!

Tools Needed:

- **3/4" Wrench** and **1/2" Wrench**

Contents Included: **4** 11mm Bolts.

